

BENCOR (Pty) Ltd.

Pumps



Connection blocks type A, B and C


The HAWES connection blocks provide the "ready for connection" feature for compact hydraulic power packs type FP, HC, MP and HK. Compact control systems can be created by directly mounting valve banks onto type A connection blocks (see also "Turn-key solutions from our modular system").

Nomenclature: Connection blocks to the completion of hydraulic power packs

Design: Add-on valve enabling pipe connection or direct mounting of valve banks

P_{max}: 700 bar

Q_{max}: approx. 20 l/min



Basic types

Basic type	Brief description	Options	Symbol
A	<p>Connection block with pressure limiting valve</p> <ul style="list-style-type: none"> • For direct pipe connection • For direct mounting of valve banks 	<ul style="list-style-type: none"> • Check valve in port P • Prop. pressure limiting valve • Reflow filter • Idle circulation valve (solenoid actuated) • Switch-off valve • Pressure limiting valve, tool or manually adjustable 	<p>Type A</p> <p>Type B</p>
B	<p>Connection block for the control of single and double acting cylinders with pressure limiting valve suitable for pipe connection</p>	<ul style="list-style-type: none"> • Check valve in port P • Throttle for the regulation of the drop rate • Idle circulation valve, open or closed in idle position • Pressure switch in port P 	
C	<p>Connection block without additional elements for direct pipe connection</p>		